

LINDOLIT® W

MOISTURE CURING LINDOLIT® W

To prevent premature drying out and shrinkage cracks

Lindolit® W (waterbased) prevents premature drying out and shrinkage cracks. To be applied on the newly poured concrete floor. Lindolit® W is a water-based acrylic dispersion with additives for instant treatment on newly installed floors.

For usage:

A first class concrete and professional installation are not enough to achieve maximum strength and durability. The after-treatment is of great importance for the final quality. The surface must not dry out too quickly, especially with higher temperatures, low humidity, draught, etc. This can result in less solidity and greater shrinkage.

Advantages: +

- Lindolit® W is water-based.
- Lindolit® W does not produce gases or vapours.
- Lindolit® W prevents too fast drying.
- Lindolit® W reduces shrinkage.
- Lindolit® W reduces possible lime precipitation.
- Lindolit® W is efficiency tested and approved (see separate test result).
- Lindolit® W can be used in combination with water and plastic film.
- Lindolit® W is used on over 5 000 000 m².

Transport & storage:

Lindolit® W is frost-susceptible.

Shelf life:

One year if properly stored.

Application:

Lindolit® W must be applied immediately after the last trowelling or as soon as possible, depending on the temperature, humidity, draught, etc. Spray Lindolit® W on and distribute evenly with a sweeper (Lindec mop).

The initial milky appearance of the Lindolit® W surface becomes transparent after a while. The correct application will produce a shiny surface after drying.

Consumption:

Art.no. 1153. Lindolit W ready to be used, shall not be diluted. Consumption: 0,20 liter / m².

Art.no. 1150. Lindolit W not deluted concentrate, to be mixed with water 1:1. Consumption (concentrate): 0,10 liter / m².

Tested:

Lindolit® W is tested according to BS 7542:1992 (European Standard).

Aftertreatment:

StainWash, which makes the surface glossy and easy to clean.

Art.no. 1150, 1153



BS 7542:1992
European
Standard

ab lindec® endeavours to provide correct information about technical properties and handling of its products. However, while ab lindec® has no control over the way in which the products are mixed and laid, or the conditions under which they set, ab lindec® can in no way be held responsible. ab lindec® is only responsible for the quality of the products at the time of delivery.

ab lindec®

Box 5, 421 21 V.Frölunda, Sweden, Tfn +46-31-298810,
Fax +46-31-298876, export@lindec.se, www.lindec.com